



TRI TOOL INC.

3806 Security Park Drive, Rancho Cordova, CA 95742-6990 USA • (916) 351-0144 • (888) TRI TOOL • FAX (916) 351-0372
www.tritool.com customer.service@tritool.com

TRI TOOL INC.
TECHNICAL SPECIFICATION
MODEL 1632 PIPEMASTER™ SYSTEM
SEPTEMBER 15, 2003

MODEL PFM 1632 PIPEMASTER™ SYSTEM

The Model PFM 1632 PIPEMASTER™ System is a portable ID mount machine tool for beveling and facing 16" through 32" pipe. The tool is configured with twin hydraulic motor drives that power helical drive gears attached to the main spindle for smoother power delivery and optimal surface finish. A set of hydraulic cylinders with rapid and slow feed control, advance and feed the cutting head into the pipe. A large diameter mandrel shaft is provided for optimum stability during heavy cutting operations. One hydraulically actuated mandrel head with extended mounting ring assemblies and mounting pads covers the complete mounting range of the tool. The lifting frame does not require removal or separate lay down stands. The tool can be lifted for mounting in horizontal, vertical-up, or vertical-down positions for prepping on site pipes.

The Model PFM 1632 PIPEMASTER™ System comes complete with:

- Model PFM 1632 Sub-Assembly 1 ea.
- I.D. Tracking Tool Module Assembly 5 ea.
- Mandrel Head Assembly 1 ea.
- Hydraulically Powered Mandrel Head Shaft Assembly 16-24 1 ea.
- Lathe Lifting Frame Assembly 1 ea.
- Drive Motor Assembly 2 ea.
- Wrench Kit 1 ea.
- Operator's Manual 1 ea.
- Mandrel Head Extension for 24-32 2 ea.

Design and Operating Features

1. The tool accepts it's own torque through the mandrel.
2. The expanding mandrel provides fast, accurate self-centering and alignment.
3. All wrenches needed for operation (less Tool Bits) are provided with the system.
4. The lathe is provided with a combination lifting frame and stand.
5. The mandrel head provides a maximum of 75,400 lbs. of clamping force (2000-PSI Hydraulic Pressure).
6. The mandrel head and adapters cover the full mounting range of the tool (16" to 32").
7. The lathe has a large diameter mandrel shaft for optimum rigidity.
8. Five and one-half (5.5) inch of feed travel allows easier and more forgiving axial positioning.
9. Five (5) I.D. tracking tool modules allows distributing the cutting loads to more tool bits to handle greater wall thickness.
10. Two (2) torque acceptance bars insure greater torque handling and better-balanced load for accurate end facing.
11. Twin hydraulic drive system delivers optimal torque at the lower RPM required for the larger pipe diameters.
12. A chip guard with a Shut-Off switch is supplied for the safety of the operator.
13. A patented interlocking safety mechanism is supplied to avoid unclamping the mandrel while the headstock is rotating.
14. A 'Jog' switch is supplied to rotate the cutting head for set up.

Specifications

1. Reference Envelope Drawing No. 77-1643.
2. Pipe Cutting Capacities
 - A. Basic Pipe Sizes

- i. Most schedules of 16" through 32" pipe.

B. Basic Tube Sizes

- i. Up to 1.88" (47.8 mm) wall tubing with a maximum O.D. of 32.00" (812.8 mm) and a minimum I.D of 13.90" (353.1 mm) may be beveled with the standard mandrel.

C. Wall Thickness Capacity

- i. Wall thickness of standard pipe schedules with wall thicknesses up to 1.88" (47.8 mm) in the range listed. Tubing or pipe with greater wall thickness may be handled provided the I.D. is equal or greater than 13.90" (353.1 mm) and the O.D. is equal or less than 32.00" (812.8 mm). Contact Tri Tool Inc. for heavier wall procedures.

3. Material Cutting Capabilities

- A. Mild steels, chrome steels (Rc 35 max), API X42 through X85, stainless steel, copper-nickel alloys and aluminum without limitations except size and wall thickness as specified in the above paragraphs.

- B. Inconel and some other high temperature alloys may require special procedures as a function of wall thickness and type of end preparations. Contact Tri Tool's Engineering Department for details.

4. Clearances and Dimensions

A. Maximum Rotating Head Dia.

- i. 40.00" (1016 mm)

B. Length (parallel to axis of pipe)

- i. 103.25 (2622.6 mm)

C. Available feed travel

- i. 5.5" (139.7 mm)

5. Drive System

A. Dual Hydraulic Drive Motor for 16" to 32" Pipe

- i. Requires a separate hydraulic power supply. (Ref: HPU 75-60/5; Technical Specifications)

- ii. Unit requirements
 - a. 60 GPM at 2000 PSI & 5 GPM at 2000 PSI.
- 6. Cutting Head Speeds
 - A. Dual Hydraulic Drive
 - i. Maximum Cutting Head Speed
 - a. 42 RPM
- 7. Mounting
 - A. Hydraulically actuated cylinder expands mandrel pins and jaw blocks.
- 8. Feed
 - A. Dual hydraulic powered cylinders with rapid positioning in both directions and fine adjustment feed for cutting.
- 9. Approximate Weight
 - A. 5200 lbs.
- 10. Power requirement
 - A. 60 G.P.M. @ 2000 P.S.I. / 5 G.P.M. @ 2000 P.S.I.

Accessories (Optional)

- 1. Short Perch Mandrel Head Kit for restricted axial mounting.
- 2. Electric 60 GPM Power Unit.
- 3. Diesel 60 GPM Power Unit.

Note To The Customer

Spare Parts and Standard Tool Bits are available from stock. Engineering design services for custom tool bits and special function modifications are available from the factory.

All Tri Tool and allied equipment products are subject to design improvements and specification changes at any time with no obligation to units already sold.

Warranty (limited): Parts and equipment are warranted against defects in material and workmanship for a period of one (1) year from date of purchase. Full details supplied on request and/or with the tools.

Filter, regulator and lubricator are required to protect the warranty on air powered tools.

